



product details

64634 HLX



Product description: 64634 HLX
 Product code: 4050300006819
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300006819

Applications	
Cooling	Forced
Burning position	p90/p15

Categorizations	
ANSI code	EFR
LIF	A1/232

General Description	
Base (standard designation)	GZ6.35
Coating	Dichroic

Logistical Data	
Product weight	27.600 g

Technical - Electrical Data	
Construction wattage	150 W
Construction voltage	15 V
Lamp voltage	15 V
Nominal wattage	150 W
Nominal voltage	15 V

Technical - Geometries	
Diameter	51.0 mm
Light center length (LCL)	32 mm
Reflector diameter [PIM]	51 mm
Length	42.00 mm

Technical - Lifespan	
Lifespan	50 h

Technical - Light Technical Data	
Focal length	32.0 mm

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300006819	Folding carton box contains 1 Piece	46,000 mm x 46,000 mm x 58,000 mm	35,600 g (0,000 g)	0,123 Cubic dec.
4050300946429	Shipping carton box contains 20 Piece	153,000 mm x 122,000 mm x 196,000 mm	788,000 g (0,000 g)	3,191 Cubic dec.

Literature

For further technical information please refer to the following OSRAM brochure: Technology and applications, Low-voltage tungsten-halogen lamps and our cross-reference-list "Halogen lamps, low and medium voltage for entertainment, technical and medical applications"



26.10.2011

Subject to change without notice. Errors and omission excepted.

© 2011 OSRAM AG

Page 1 of 1