

Catalogue No: **S125NN3**

TB2 MCCB 125 FRAME 3P 125A NON AUTO SWITCH

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 125 AF > Non Auto Switch Disconnecter 125 AF



T2 MCCB NON AUTO 125A 3P

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	TemBreak 2 MCCB
Component Type MCCB	Switch Disconnecter (Non-auto)
In, Rated Current at 45°C	125 A @45°C
Icm, Rated Short Circuit Making Capacity	3.6 kA Peak
Icw, Short Time Withstand Current, 300ms (rms)	2 kA, 300ms
Frame Size	125 AF size
Number of Poles	3
Ui, Rated Insulation Voltage	800 V (rms)
Height	155 mm
Width	90 mm
Depth	68 mm
Weight	1.1 kg
Standard Installation Method	Front Connection
Electrical Service Life at Un, In	30000 cycles
Mechanical Service Life	30000 cycles
Standards Compliance	IEC 60947-2 AS/NZS 60947-2
Certifications	CE
Shipping Approvals	Contact NHP

Catalogue No: **S125NN3**

TB2 MCCB 125 FRAME 3P 125A NON AUTO SWITCH

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 125 AF > Non Auto Switch Disconnecter 125 AF



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -