

Spitfire 1 LED Surface Mount Weather Proof Proof

- Compliance to latest AS/NZS2293.3:2018.
- Reliable Stanilite Brand.
- Hi-temp NiCad batteries.



Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Emergency Lighting	Spitfire
Testing System		Single Point Unit
Operating Mode		Non-Maintained
Operating Voltage		240 VAC
Power Consumption		1.0 W
Mounting		Surface - Ceiling
LED Life		100,000 hours
Photometric Classification		C0:D40 C90:D40
Battery Type		Ni-Cd
Height		130 mm
Width		188 mm
Depth		278 mm
Base Colour		Grey
Battery Replacement		0301220
IP Rating		IP67
Standards Compliance		AS/NZS CISPR 15 AS/NZS2293.3:2018 AS/NZS60598.1:2017 AS/NZS60598.2.22:2005



REFERENCES

IECEX Certificate

-

Supplier Declaration of
Conformity:

[Spitfire Weatherproof Emergency, NiCad or LifePO4 Battery_Supplier Declaration of Conformity \(SDoC\)](#)

Installation Guide:

-

User Manual:

-

Manufacturer Datasheet:

-

Manufacturer Catalogue
& Product Selection:

-