

Cable gland nylon black ISO/M20 Ø 10-14 mm IP68



Characteristics

Mounting Hole (mm) : **20.2**  
 Minimum cable Ø (mm) : **10**  
 Maximum cable Ø (mm) : **14**  
 Inside Ø (mm) : **14.4**  
 Quantity : **30**  
 Selling unit : **Each**

Norms

> IP 68

Compliance marks



GENERAL INFORMATION

Description

Contents: locknut, washer, body, seal and nut.

Technical details

Material: UL approved polyamide 6.6.  
 Flammability: UL 94V-2.  
 Operating temperature: -20 °C + 100 °C  
 Metric Pitch: 1.5 mm.  
 Colour: black.  
 Halogen free.

Application(s)

Can be mounted directly onto pre-drilled panel hole using the locknut or can be directly screwed onto metric threaded holes.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 4.4  
 Length (cm) : 3.4  
 Depth (cm) : 3.4  
 Net weight (kg) : 0.01  
 Gross weight (kg) : 0.01



Outer package 1



Carton box

Height (cm) : 12  
 Length (cm) : 17  
 Depth (cm) : 9  
 Net weight (kg) : 0.51  
 Gross weight (kg) : 0.51



x 30

Outer package 2



Carton box

Height (cm) : 31.5  
 Length (cm) : 61  
 Depth (cm) : 37  
 Net weight (kg) : 13.89  
 Gross weight (kg) : 14.96



x 900