

PV-ezRack SolarRoof-Black Anodized

PV-ezRack SolarRoof is an universal mounting system for PV installation on roof, which is available for black and silver. The components are easy to install and can be used for flush as well as tilted systems, on a large variety of roof types. The interfaces, rails and clamps use high quality, robust and corrosion resistant materials including structural grade aluminium alloy (AL6005-T5) and stainless steel (SUS304).

Main Benefits

Quick and easy installation

Innovative and internationally patented, the Z-Module technology is used in almost all SolarRoof components. The Z-Module provides a quick, easy and safe installation method. It can be inserted in to the rail at any given point, and secured with just three hand grips.

Versatility

A large variety of tin roof fixings, tilt legs and adapters help ensure that you will find a suitable fixing method for almost every roof, where fixing with or without penetration is required.

Wide range of tilting

With three adjustable tilt legs, these parts can tilt panels from between 10-60 degrees. Through its innovative design, the tilt legs can cope with all common purlin distances.

Universal

SolarRoof has suitable mid and end clamps for every size of solar panel including frameless, thin film panels or special clamps for cyclonic regions. In the growing range of clamps, cable clips, adapters and accessories you're sure to find the parts you require for your residential rooftop mounting needs.



C-U/30/46/BA C-U/30/46-G/BA

Universal Clamp

PV-ezRack Universal Clamp, with dual functionality (inter and end clamp), is applicable with most common framed PV modules from 30 mm to 46mm in height. Inbuilt grounding clip is also available.



ER-EC-STXXB ER-IC-STXXB

Inter and End Clamps


The PV-ezRack Inter and End clamps offer a simple, easy to use and robust fixing of the PV panels (of all sizes) using the patented Clenergy Z-module. Compatible clamps for thin film modules are also available.



ER-TL-10/15/BA ER-TL-15/30/BA

Tilt Legs

The available adapters, non-penetration clamps and base rails make the application of this part truly universal.



Available accessories

- Isolator Shade 
- Rail caps 



ER-R-ECO/BA

ECO Rail


Specifically developed to achieve larger spans, the SolarRoof ECO-Rail has reduced the number of required fixings. The ECO-Rails have two patented Z-Module channels with one at top for panel mounting and the second on side for connecting to the roof interface. The ECO-Rail comes in 4200mm and 4400mm lengths.



ER-SP-ECO/BA

Splice for ECO Rail

Using high-quality aluminum material and stainless steel bolts, the ECO Rail Splice allows for convenient extension of rails without on-site cutting and processing.



ER-I-05/BA ER-I-25/BA EZ-AD-C43/BA

Tin Interface

The robust aluminium L-feet, which provides a height adjustment of almost 30mm, is designed for corrugated and trimdek type tin roofs. It comes with a Z-Module or Click Module plus bolt preassembled, with a screw which includes bonded sealing washer plus an EPDM rubber pad.

Materials

AL6005-T5 | SUS304

Contact us or one of our qualified resellers for a personalised quotation today.

10 Year Warranty* **Commercial** **Residential**

International Patent PCT/AU2009/000616

*see Clenergy PV-ezRack warranty for further details