



CLEVERTRONICS L10 600MM (2FT) NON-MAINTAINED BATTEN REPLACEMENT



PRODUCT INFORMATION

Catalogue Number	LBS2N-ZW
Description	L10 Optimum 600mm (2ft) Non-Maintained Bare Batten Replacement Utilising the Lifelight - High Performance, Emergency Light
Construction	Powder coated Steel body and ABS/Polycarbonate End Caps
Mounting	Surface Mount
Dimensions L x W x H	610mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT.
1100930	CLIFE Head Assembly, Round, 1LED
LLIFE-CKIT	Lifelight: LED, Control Only, L10
8001450	PCA:Powerline Node ZW, #CT10310-A6

