

CLEVERTRONICS L10 LIFELIGHT PRO SURFACE MOUNT



PRODUCT INFORMATION

Part Number	LLIFE-2PRO-SMS-600
Description	L10 Lithium Nanophosphate LifeLight PRO, high performance, surface mount twin Emergency Light, Enabled with Clevertest Plus
Construction	Powder coated metal enclosure PC/ABS head
Mounting	Surface mount and can also be chain suspended
Dimensions L x W x H	613mm x 112mm x 55mm
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 4.4 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D125 C ₉₀ =D125

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
1100830	Lifelight Pro Head Assembly, Round

