

Catalogue No: **MAS0406021R5**

ENCLOSURE W/MOUNT M/STEEL IP66 H400 x W600 x D210mm S/DOOR

Enclosures and Climate Control > Standard Enclosures > Wall Mount Enclosures > Wall Mount Enclosures - Mild Steel > Wall Mount Enclosures - MAS Single Door > MAS Single Door Wall Mount Enclosures - RAL 7035 Light Grey (Includes Mounting Plate)



Enclosure Wall Mount Mild Steel IP66 H400xW600xD210mm Single Door

- Over 50 stocked sizes ensuring you have a high quality product ready for any situation in exactly the right size
- IP66 (MAS) / IP55 (MAD) and IK10 protection with fully folded and seam welded mild steel construction providing the highest protection for your internal components, for a range of indoor applications (NOTE - Optional glazed door models are IP55 / IK08)
- Wall fixing holes are pressed out 2mm allowing for the enclosure to lay on its back with no damage to the rear
- Strengthened over folded front frame serves as a gutter to keep liquids away from the polyurethane gasket
- Concealed hinges with captive hinge pins provide 130° opening and clean smooth lines, plus easy removal for maintenance and extra resistance to vibration
- Gland plate installed as standard towards the rear of the enclosure to make for easy wiring
- Comes with galvanised mounting plate as standard with gland plate opening same width as mounting plate for easy installation. Mounting plate is marked at 10mm intervals for easy horizontal positioning of equipment
- Reversible door allows for flexibility in installation with the same enclosure able to be used in double the applications
- A large range of custom locking options available to replace the standard 3mm double-bit lock
- Recommended for indoor use only.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	MAS Wall Mount (Single Door)
Material, Body / Housing	Powder Coated Mild Steel material
Enclosure Load Capacity	160 kg
Door Load Capacity	28 kg
Door Mounting Profiles	Not included, however studs for mounting MMDP door profiles are included on the door
NEMA Enclosure Class (NEMA 250:2003)	Type 4 Type 12 Type 13
Material thickness, body / housing	1.2 mm
Colour, Body / Housing	Light Grey (RAL 7035) colour
Finish, body / housing	Ripple body/housing
Details, body / housing	Folded and seam welded. Four 8.5mm diameter holes for wall fixing, pressed out in 20.4mm diameter x 2mm depressions to allow air circulation around the rear part of the enclosure.

Catalogue No: **MAS0406021R5**

ENCLOSURE W/MOUNT M/STEEL IP66 H400 x W600 x D210mm S/DOOR

Enclosures and Climate Control > Standard Enclosures > Wall Mount Enclosures > Wall Mount Enclosures - Mild Steel > Wall Mount Enclosures - MAS Single Door > MAS Single Door Wall Mount Enclosures - RAL 7035 Light Grey (Includes Mounting Plate)



Height	400 mm
Width	600 mm
Depth	210 mm
Weight	13.4 kg
IP Rating	IP66
IK Rating	IK10
Material, door	Powder Coated Mild Steel
Material thickness, door	1.2 mm
Colour, Door	Light Grey (RAL 7035) door
Finish, Door	Ripple door
Hinge Type	Reversible, Concealed Hinges with Captive Pin
Opening Range	130 °
Details, door	180 degree hinging available as accessory
Mounting Plate Included	Yes
Material, Mounting Plate / Bracket	Zinc Galvanized Steel
Material Thickness, Mounting Plate / Bracket	2 mm
Height, Mounting Plate	370 mm
Width, Mounting Plate	550 mm
Details, Mounting Plate / Bracket	Marked vertically at 10mm intervals for easy horizontal positioning of equipment, fixed onto M8 welded studs with extra holes top and bottom to facilitate cable fixing.
Gland Plate(s) Included	Yes
Number of Gland Plates	1 qty
Material, Gland Plate	Powder Coated Mild Steel
Material Thickness, Gland Plate	1.4 mm
Colour, Gland Plate	Light Grey (RAL 7035) gland plate
Finish, Gland Plate	Ripple gland plate
Height, Gland Plate	510 mm height
Height, Gland Plate Opening	510 mm opening height
Width, Gland Plate	96 mm width
Width, Gland Plate Opening	96 mm opening width
Details, Gland Plate	1 Opening, Type 4
Material, Gasket / Seal	PUR / PU material
Details, Gasket / Seal	Single piece, Injected
Details, earthing	Earthing studs M8x12mm in body and cover, M8 nuts, earth washers and earth labels
Number of Locks	1 qty
Lock Type	DIN - 1/4 Turn type
Diameter, Lock	3 mm
Material, Lock	Plastic material
Delivery Details	Enclosure with mounting plate and door, gland plate(s) with gasket(s), plastic DIN 3mm key, mounting and earthing accessories.
Standards Compliance	NEMA 250:2003
Certifications	C-UL CE GOST-R KEMA UL

Catalogue No: **MAS0406021R5**

ENCLOSURE W/MOUNT M/STEEL IP66 H400 x W600 x D210mm S/DOOR

Enclosures and Climate Control > Standard Enclosures > Wall Mount Enclosures > Wall Mount Enclosures - Mild Steel > Wall Mount Enclosures - MAS Single Door > MAS Single Door Wall Mount Enclosures - RAL 7035 Light Grey (Includes Mounting Plate)




Shipping Approvals

Lloyd's Register of Shipping
DNV-GL (Det Norske Veritas Germanischer Lloyd)

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-



Dimension Diagram

Catalogue No: **MAS0406021R5**

ENCLOSURE W/MOUNT M/STEEL IP66 H400 x W600 x D210mm S/DOOR

Enclosures and Climate Control > Standard Enclosures > Wall Mount Enclosures > Wall Mount Enclosures - Mild Steel > Wall Mount Enclosures - MAS Single Door > MAS Single Door Wall Mount Enclosures - RAL 7035 Light Grey (Includes Mounting Plate)



Complete enclosure						Standard enclosure with mounting plate and lock		Standard enclosure with mounting plate, lock and glazed door	
Standard dimensions (mm)	Mounting plate dimensions (mm)	No. of gland plates	No. of glands	Weight (kg)	Price Cat. No.	Weight (kg)	Price Cat. No.	Weight (kg)	Price Cat. No.
200 200 155 170 150 137	1	1	1	1.0	MAS0201585	N/A			
300 255 170 250 137	1	1	1	1.8	MAS0301585	N/A			
210 250 155 220 200 137	1	1	1	1.0	MAS0215185	N/A			
300 250 155 270 200 137	1	1	1	1.6	MAS0301585	N/A			
300 330 170 350 137	1	1	1	2.2	MAS0301585	MAS03001585			
300 330 170 350 137	1	1	1	2.5	MAS0301585	MAS03001585			
300 330 170 400 137	1	1	1	3.2	MAS0301585	MAS03001585			
350 250 155 400 200 137	1	1	1	3.3	MAS0301585	MAS03001585			
400 300 210 370 250 137	1	1	1	4.7	MAS0402185	MAS04001585			
400 370 370 350 137	1	1	1	8.6	MAS0402185	MAS04001585			
400 370 370 400 137	1	1	1	10.5	MAS0402185	MAS04001585			
400 370 370 500 137	1	1	1	12.2	MAS0402185	MAS04001585			
500 300 210 470 250 137	1	1	1	8.6	MAS0502185	MAS05001585			
500 300 470 250 242	1	1	1	9.2	MAS0502185	MAS05001585			
400 370 470 350 137	1	1	1	10.4	MAS0402185	MAS04001585			
400 300 470 350 242	1	1	1	11.2	MAS0402185	MAS04001585			
400 300 470 350 242	1	1	1	11.1	MAS0402185	MAS04001585			
500 370 470 400 137	1	1	1	12.6	MAS0502185	MAS05001585			
500 300 470 400 242	1	1	1	14.3	MAS0502185	MAS05001585			
400 400 210 570 350 137	1	1	1	12.2	MAS0602185	MAS06001585			
400 300 570 350 242	1	1	1	14.1	MAS0602185	MAS06001585			
500 370 570 400 137	1	1	1	14.4	MAS0602185	MAS06001585			
500 300 570 400 242	1	1	1	17.5	MAS0602185	MAS06001585			
600 370 570 500 137	1	1	1	17.1	MAS0602185	MAS06001585			
600 300 570 500 242	1	1	1	21.0	MAS0602185	MAS06001585			
400 300 570 500 242	1	1	1	24.0	MAS0602185	MAS06001585			
600 400 570 500 242	1	1	1	27.0	MAS0602185	MAS06001585			
400 300 570 750 242	2	1	1	31.0	MAS0602185	MAS06001585			

Technical Diagram