

## CLEVERTRONICS LP LIFELIGHT PRO SQUARE



## PRODUCT INFORMATION

Part Number	CLIFE-PRO-SQ
Description	LP Premium LifeLight PRO, high performance, square recessed Emergency Light, Enabled with Clevertest Plus
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm x 60mm (Head)
Ceiling Hole Cut-Out	51mm
Minimum Ceiling Depth	200mm
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 4.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D63 C <sub>90</sub> =D63

## REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
CLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP Lithium
1100840	Lifelight Pro Head Assembly, Square

