

Perforated zinc plated metal half saddles 25 mm 6.5 mm Ho (x 100)



Characteristics

Ø (mm) : **25**
 Ø1 (mm) : **6.5**
 H (mm) : **26.8**
 L (mm) : **59.5**
 L1 (mm) : **45.7**
 W (mm) : **25.2**
 Thickness (mm) : **1.2**
 Quantity per box : **100**
 Selling unit : **Each**

Benefits

- Quick and easy installation: "Clips" feature for snapping and positioning the saddles onto conduit before securing it.
- Reinforced rib for extra strength.

GENERAL INFORMATION

Technical details

Material: steel Q235.
 Coating: blue-white zinc galvanized, ≥ 5 µm.

Application(s)

Used to secure and mount electrical cables and conduits to a variety of work surfaces.
 For indoor and outdoor application.

LOGISTIC INFORMATION

Packaging



Plastic box

Height (cm) : 12.3
 Length (cm) : 16.5
 Depth (cm) : 12
 Net weight (kg) : 2.05
 Gross weight (kg) : 2.15



Outer package 1



Carton box

Height (cm) : 14
 Length (cm) : 62
 Depth (cm) : 35
 Net weight (kg) : 22
 Gross weight (kg) : 23



x 10.00

Outer package 2



Pallet

Height (cm) : 130
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 743
 Gross weight (kg) : 749



x 330.00